



			I		
			III	II	
Operating temperature range[°C]					
Max. operation altitude[m]					
Storage temperature[°C]					
Typical noise emission[dBA]					
Self-consumption at night [W]					
			(	)	
Warranty[Years]					
() [mm]					
Weight[KG]					

Nominal Battery Pack Energy[KWh]			
Available Battery Pack Energy[KWh]			
Nominal Battery Cell Capacity[Ah]			
Nominal Voltage[V]			
Nominal Charging Current[A]			
Nominal Discharging Current[A]			
Warranty[Years]			
Dimension[mm]			
Weight[Kg]			

Nominal Battery Pack Energy[KWh]				
Available Battery Pack Energy[KWh]				
Nominal Battery Cell Capacity[Ah]				
Nominal Voltage[V]				
Nominal Charging Current[A]				
Nominal Discharging Current[A]				
Warranty[Years]				
Dimension[mm]	()	()	()	()
Weight[Kg]				



HIENERGY SERIES G2 THREE PHASE RESS

LEADING ODM PROVIDER OF GREEN ENERGY PRODUCTS

ODM VALUE CHAIN
A REPEATABLE PATH FOR EXCELLENCE IN QUALITY DELIVERY

Central Academy
Industrial Technology Research Institute
Industrial Technology Research Institute
AI Research Institute

Beijing & Anqing Manufacturing Cneter

- Mechanical back-to-back test
- Simulation test
- Motor Load Test

HIENERGY SERIES G2 THREE PHASE RESS

PRODUCT PARAMETER

Max. PV array power[W]

Max. open circuit voltage[V]

Max. input current per string[A]

Max. short circuit current per string[A]

MPPT voltage range[V]

Start operating voltage[V]

 SUPERIOR PERFORMANCE

- •
•
•

FLEXIBLE APPLICATION

- •
•
•

○ INTEGRATED CONTROL

-
-
-
-

 TRUSTED RELIABILITY

-
-
-
-